


# Micro

Low-friction Micro blocks are compact and lightweight, with fast trim and release under high or low loads. Ideal for sailboards, smaller dinghies, and for lightly loaded control lines on boats of all sizes.

Free-rolling Delrin® ball bearings, sheave and sideplates UV-stabilized, with carbon-black additive for maximum protection. Stainless steel sideplates for strength.

**Use for:**

- Cunninghams/outhauls
- Vangs
- Traveler controls
- Barberhaulers
- Flag halyards
- Leech cords
- Lead car return tackles



Sheave diameter offset to spread falls and eliminate line chafe

Free-rolling large-diameter Delrin® sheaves

244

Micro fiddle with rounded V-jam, or triples with cam make compact self-cleaning tackles

Spacer keeps line in sheave



Cutout  
5/8" (16 mm) x 1 1/16" (40 mm)



Sheaves see page 103.

Part No.	Description	Sheave Ø		Length		Weight		Max line Ø		Shackle pin Ø		Safe working load		Breaking strength	
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg
224	Single	7/8	22	1 1/2	38	1/2	14	1/4	6	—	—	200	91	1200	544
225	Single/becket	7/8	22	2	51	3/4	21	1/4	6	—	—	200	91	1200	544
226	Double	7/8	22	2	51	1 1/2	43	1/4	6	—	—	350	159	1200	544
227	Double/becket	7/8	22	2 1/2	64	1 1/2	43	1/4	6	—	—	350	159	1200	544
228	Triple	7/8	22	2	51	2	57	1/4	6	—	—	500	227	1200	544
229	Triple/becket	7/8	22	2 1/2	64	2 1/4	64	1/4	6	—	—	500	227	1200	544
230	Triple/423 Carbo-Cam®	7/8	22	2	51	3 1/2	99	1/4	6	—	—	500	227	1200	544
231	Triple/423 Carbo-Cam®/becket	7/8	22	2 1/2	64	3 1/2	99	1/4	6	—	—	500	227	1200	544
232	Traveler	7/8	22	2 3/4	71	1 1/4	35	1/4	6	—	—	200	91	1200	544
233	Cheek***	7/8	22	2 1/2	64	3/4	21	1/4	6	—	—	200	91	1200	544
234	Single/shackle	7/8	22	2 1/4	57	3/4	21	1/4	6	3/16	5	200	91	1200	544
235	Single/shackle/becket	7/8	22	2 3/4	71	1	28	1/4	6	3/16	5	200	91	1200	544
242	Thru-deck***	7/8	22	2 5/8	67	1	28	1/4	6	—	—	200	91	1200	544
243	Upright***	7/8	22	1 1/2	38	1	28	1/4	6	—	—	200	91	1200	544
244	Fiddle/V-jam*	7/8	22	3 1/2	89	2	57	1/4	6	3/16	5	350	159	1200	544
245	Fiddle/V-jam/becket**	7/8	22	4	102	2	57	1/4	6	3/16	5	350	159	1200	544
292	Single/swivel	7/8	22	2 3/8	60	1	28	1/4	6	5/32	4	200	91	1200	544
377	Forkhead	7/8	22	1 21/32	42	9/16	16	1/4	6	—	—	200	91	1200	544
443	Block/eyestraps assembly†	7/8	22	1 3/4	45	9/16	16	1/4	6	—	—	200	91	1000	454

\*Use w/225 or 235 \*\*Use w/226 \*\*\*#10 (5 mm) RH fasteners †#8 (4 mm) RH fasteners