

Cruising ESP Blocks

Cruising ESP (Elegant Simple Products) is a line of hardware that complements our existing blocks in looks and function, but is simpler in design and construction. Sheaves feature axle bearings to handle high static loads, and are ideal for halyards or limited purchase systems on cruising boats.

Footblocks

Use for reef lines and genoa sheets where the angle is not extreme.

Mastbase

Use teardrop-shaped blocks for direct attachment to padeyes or mast collar posts to keep lines extremely close to the deck.

Use the 6050 and 6056 on production boats with mounting posts on the mast collar. The 6057 and 6065 padeye-mounted blocks have hourglass-shaped head spacers to seat on the padeye bale.

Swivels and Fiddles

Use swivel and fiddle blocks in winch-driven purchases of 4:1 or less. Shackles lock at 90-degree intervals or swivels freely. Perfect for vang or mainsheet systems on cruising boats from 35 ft to 45 ft (10 to 14 m).

Use the 6099 for vangs, preventers, or mainsheet systems on boats with long booms and low aspect sails. Ideal as runners on masthead boats to minimize mast pumping.

Flip block over to mount on opposite side of boat

6077
6078



Can be double stacked


Lockoff to temporarily secure sheets

Lockoff blocks feature aluminum sheaves



Plastic sleeve bearing for high static loads

Ball bearings handle low loads and side loads from unfair leads



6091
6092
6093



Sun Odyssey 45 — Photo Courtesy of Jeanneau



Refer to page 92 for 6077/6078/6091/6092/6093 hole spacing.

Part No.	Description	Sheave Ø		Length		Weight		Clevis pin Ø		Max line Ø		Safe working load		Breaking strength		Max lockoff load		Fasteners (FH)	
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg	lb	kg	in	mm
57 mm																			
6050	Mastcollar	2 1/4	57	3 11/16	93.5	4.3	122	5/16	8	5/8	16	2100	850	4190	1900	—	—	—	—
6065	Padeye block	2 1/4	57	3 11/16	93.5	4.5	128	5/16	8	5/8	16	2100	850	4190	1900	—	—	—	—
6077	Footblock/lockoff** ‡	2 1/4	57	3 7/8	99	8	226	—	—	3/8	16	2500	1135	5000	2272	1200	550	5/16	8
6091	Footblock‡	2 1/4	57	3 7/8	99	5.4	153	—	—	3/8	16	2500	1135	5000	2272	—	—	5/16	8
6095	Mastcollar/low-load	2 1/4	57	4 5/8	117	4	113	—	6	5/8	16	1650	750	3300	1500	—	—	—	—
6096	Narrow Mastcollar	2 1/4	57	3 1/2	89	3.3	94	—	6	3/8	10	1650	748	3300	1497	—	—	—	—
6097	Narrow Mastcollar	2 1/4	57	3 1/2	89	3.5	99	5/16	8	3/8	10	1650	748	3300	1497	—	—	—	—
75 mm																			
6056	Mastcollar	3	75	4 5/8	117	7.8	221	5/16	8	3/4	19	3000	1361	6000	2721	—	—	—	—
6057	Padeye block	3	75	4 11/16	119	8.4	238	3/8	10	3/4	19	3500	1587	7000	3175	—	—	—	—
6078	Foot/lockoff** ‡	3	75	4 5/8	112	12	340	—	—	3/4	19	3500	1587	7000	3175	1200	550	5/16	8
6092	Footblock‡	3	75	4 5/8	112	10.3	293	—	—	3/4	19	3500	1587	7000	3175	—	—	5/16	8
6098	Narrow Mastcollar	3	75	4 7/16	113	6.4	181	5/16	8	1/2	12	2500	1134	5000	2268	—	—	—	—
100 mm																			
6093	Footblock‡	4	100	5 11/16	144	22.6	642	—	—	3/4	19	7500	3402	15000	6804	—	—	1/2	12

**Lockoffs are intended to hold lines temporarily and should not be used in place of line stoppers or clutches

‡If double stacked, upper block is two-thirds of listed SWL and breaking strength