

Stainless Steel Cruising ESP

Add dazzle to your boat with elegant stainless steel blocks. Sideplates are polished to a high luster to reflect your boat's beauty, whether it's classic wood, or a modern cruiser.

Sheaves

Cruising ESP sheaves feature axle bearings to handle high, static loads and sideload balls so sheaves spin freely when loads are released. They are perfect for halyards or limited purchase systems on cruising boats. Cruising ESP blocks are easy to install. Footblocks and deck organizers can be double stacked.

Teardrops

Teardrop blocks keep lines close to the deck and are used for mast collars with integral swivel posts. Perforated mast collars, or mastbase situations where the lead may change, require swivel blocks.

Footblocks

Footblocks are available with lockoffs to temporarily secure sheets. A single block works for either port or starboard applications by flipping it over.

Swivels and Fiddles

Use Cruising ESP swivel and fiddle blocks in winch-driven purchases of 4:1 or less. Perfect for vang or mainsheet systems on cruising boats from 35 ft to 45 ft (10 m to 14 m).

Set screw in three-way head locks shackle in front or side positions, or lets block swivel to keep line from twisting

Swivels handle changing leads

Shackle attaches to perforated mast collars

Riveted construction keeps sideplates clean

Plastic sleeve bearing for high static loads

Strong stainless steel sideplates with mirror finish

Ball bearings handle low loads and side loads from unfair leads



Whimsical, Malö 45, Leif Ångermark designer — Rick Tomlinson Photo

Part No.	Description	Sheave Ø		Length		Weight		Clevis/Shackle pin Ø		Max line Ø		Safe working load		Breaking strength‡		Max lockoff load		Fasteners (RH)	
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg	lb	kg	in	mm
57 mm																			
6068	Single/swivel	2¼	57	5½	140	11	312	5/16	8	5/8	16	2500	1135	5000	2272	—	—	—	—
6069	Mastcollar	2¼	57	311/16	93.5	7	198	5/16	8	5/8	16	2500	1135	5000	2272	—	—	—	—
6070	Single foot/lockoff* ‡	2¼	57	3¾	132	9	255	—	—	5/8	16	2500	1135	5000	2272	650	295	3/8	10
75 mm																			
6072	Single/swivel	3	75	6¼	159	19	539	5/16	8	¾	19	3500	1587	7000	3175	—	—	—	—
6073	Mastcollar	3	75	45/8	117	16	454	5/16	8	¾	19	3000	1361	6000	2721	—	—	—	—
6074	Single foot/lockoff* ‡	3	75	43/8	111	17	482	—	—	¾	19	3500	1587	7000	3175	750	340	3/8	10
Deck Organizers																			
6071	Deck organizer/3-sheave‡	2¼	57	915/16	252	21	595	—	—	5/8	16	6000	2721	12000	5442	—	—	3/8	10
6075	Deck organizer/3-sheave‡	1½	40	711/16	179	10	284	—	—	½	12	3000	1361	6000	2721	—	—	5/16	8

*Lockoffs are intended to hold lines temporarily and should not be used in place of line stoppers or clutches
‡If double stacked, upper block/organizer is two-thirds of listed SWL and breaking strength