

Micro CB Cars

Micro Captive Ball Traveler Cars are used on small dinghies and catamarans. The one-piece solid aluminum construction is lightweight and strong. Machined aluminum Hardkote-anodized races permit Torlon® balls to transition smoothly from the active-to-return race for smooth trimming or easing. Stainless steel wire guides keep the balls captive when the car is off the track. Pivoting shackle cars have low pivot points to handle non-vertical loads.

2703 Ti-Lite cars matched with Ti-Lite blocks provide the ultimate, lightweight, low-profile system. High-tech line replaces shackles and spring. Control lines attach with a loop splice or clove hitch. Consult Use Chart on page 117 to size traveler to mainsail area.

Use for:

- Mainsheet cars
- Jib sheet cars
- Vangs on small dinghies
- Controls on small keelboats



Mercury — UnderTheSunPhotos.com Photo

Part No.	Description	Length		Width		Car body height		Weight		Safe working load		Breaking strength	
		in	mm	in	mm	in	mm	oz	g	lb	kg	lb	kg
2700	Car/pivoting shackle	2 ³ / ₁₆	56	1 ⁷ / ₁₆	40	3/ ₄	19	1.76	50	310	140	1500	680
2701	Car/pivoting shackle/control blocks	3 ⁷ / ₁₆	87	1 ⁷ / ₁₆	40	3/ ₄	19	2.56	73	310	140	1500	680
2702	Car/pivoting shackle/tangs	2 ³ / ₁₆	61	1 ⁷ / ₁₆	40	3/ ₄	19	2.08	59	310	140	1500	680
2703	Ti-Lite car	2 ³ / ₁₆	56	1 ⁷ / ₁₆	40	3/ ₄	19	1.6	45	310	140	1500	680

See page 43 for replacement balls