



## MKIII Unit 3.25 Typical Boat Length 55' - 70' (16.8 - 21.3 m)

Wire Ø (1 x 19 SS)	Rod Ø	Clevis Pin Ø
5/16" (14 mm)	-40, 12.7 mm	7/8", 1" (22.2, 25.4 mm)

Max. Dyform® size 1/2" or 12 mm - Specify special Dyform® wedge.

<b>Headstay Length</b>	Standard 74'9" (22.78 m); max 88'9" (27.05 m)
------------------------	---

Part No.	Description
1080	Furling system for <b>wire</b> *
1081	Furling system for <b>rod</b> *

<b>Headstay Terminal Required- sold separately</b>
--

1034	Sta-Lok® 5/16" (14 mm)
1035 -40	Rod -40 (12.7 mm) Navtec®
1035 12.7mm	Rod -40 (12.7 mm) Riggarna®

<b>Optional Parts</b>
-----------------------

958	Extra 7' (2.13 m) luff foil extrusion
1032	Extra 10" (254 mm) connector for <b>wire</b>
960	Extra 10" (254 mm) connector for <b>rod</b>
945	Halyard restrainer (use only when required)

\*Line not included Consult Harken® if boat length or headstay length exceeds specifications above

## MKIII Unit 3.5 Typical Boat Length 65' - 80' (19.8 - 24.4 m)

Wire Ø (1 x 19 SS)	Rod Ø	Clevis Pin Ø
5/8", 3/4" (16, 19 mm)	-48, 14.3 mm	7/8", 1", 1 1/8" (22.2, 25.4, 28.57 mm)

Max. Dyform® size 14 mm - Requires custom Sta-Lok® terminal. Contact Harken®.

<b>Headstay Length</b>	Standard 76'10" (23.42 m); max 94'10" (28.91 m)
------------------------	---

Part No.	Description
1082	Furling system for <b>wire with stud</b> *
1083	Furling system for <b>rod with stud</b> * (specify Navtec® or Riggarna®/OYS)

<b>Optional Parts</b>
-----------------------

1079	Extra 9' (2.74 m) luff foil extrusion
1066	Extra 10" (254 mm) connector

\*Line not included

## MKIII Unit 4 Typical Boat Length 75' - 90' (22.9 - 27.4 m)

Wire Ø (1 x 19 SS)	Rod Ø	Clevis Pin Ø
7/8" (22 mm)	-60, 16.75 mm, -76, 17.91 mm	1 1/4", (31.8 mm)

Max Dyform® size 19 mm - Requires custom Sta-Lok® terminal. Contact Harken®.

<b>Headstay Length</b>	Standard 87'5" (26.64 m); max 114'5" (34.87 m)
------------------------	--

Part No.	Description
1084	Furling system for <b>wire</b> *
1085	Furling system for <b>rod with stud</b> * (specify Navtec® or Riggarna®/OYS)

<b>Optional Parts</b>
-----------------------

1086	Extra 9' (2.74 m) luff foil extrusion
1069	Extra 12" (305 mm) connector

\*Line not included **Continuous rod only. If sectional order 4.5**

## MKIII Unit 4.5 Typical Boat Length 85' - 110' (25.9 - 33.5 m)

Wire Ø (1 x 19 SS)	Rod Ø	Clevis Pin Ø
1" (25 mm)	-76 (17.91 mm), -91 (19.50 mm), -115 (22.20 mm)	1 1/4", 1 3/8", 1 7/8" (31.8, 34.9, 39.7 mm)

<b>Headstay Length</b>	Standard 102'10" (31.34 m); max 126'10" (38.67 m)
------------------------	---

Part No.	Description
1087	Furling system for <b>wire</b> *
1088	Furling system for <b>rod with stud</b> * (specify Navtec® or Riggarna®/OYS)

<b>Optional Parts</b>
-----------------------

1050	Extra 12' (3.66 m) luff foil extrusion
1051	Extra 13 1/2" (343 mm) connector

\*Line not included

### Optional Parts



960  
1032  
1066  
1069  
1051



958  
1079  
1086  
1050



945