

# Cam Cleat Accessories

Use these accessories to adapt our cleats for many applications. Whether you need to clean up your cockpit controls with color-coding, or lead a line cleanly to the cleat, we've got the perfect accessory for you.

Lightweight cam fairleads mount either aft or ahead of the cam. Mounted behind the cleat, they allow engagement and release up to 45° to the side of the cleat. The stainless tubes protect lines and the smooth contours prevent hang-ups. Wire fairleads maintain a low profile while holding the line close to the cleat. The X-Treme Angle Fairlead allows releasing and recleating at angles up to 90° to the cleat. This sets it apart from other fairleads where line uncleats at extreme angles, and can't recleat without centering the line. The low-friction stainless bail provides a bullet-proof turning point. Perfect for traveler and cabintop controls or deck cleats—a must for the new Laser® deck cleating system.

Low-profile top-mounted fairleads can also be used to guide lines. They feature stainless wear-guards for long life and are available in various colors for color-coding your cams. We offer a wide range of eyestraps to hold line at the cleat and to provide fair leads.



Stainless steel loop provides low-friction turning post

Cleat and uncleat at angles up to 90 degrees

Base plate ensures optimal cleating height

Ideal for Laser® outhaul/cunningham controls

372

Use with risers and angled wedges

Part No.	Description	Height above cam		Height		Length		Width		Weight		Fastener Spacing		Fits
		in	mm	in	mm	in	mm	in	mm	oz	g	in	mm	
Micro														
281	Eyestraps	1/2	12	—	—	17/16	36	7/16	11	.16	4.5	11/16	27	338/423
284	Wire fairlead	—	—	13/16	21	17/8	48	15/16	24	.24	7	11/16	27	338/423
293	Flat cam riser	—	—	5/8	16	17/8	48	15/16	24	.50	14	11/16	27	338/423
294	15° Angled micro cam riser	—	—	3/4	19	17/8	48	15/16	24	.75	21	11/16	27	338/423
297	Cam wedge kit	—	—	—	—	17/8	48	15/16	24	.16	5	11/16	27	338/423
329	Fairlead	9/16	14	—	—	17/16	37	2	51	.57	16.3	11/16	27	338/423
372	X-Treme Angle Fairlead	7/8	22	—	—	15/16	33	2	51	.96	27.2	11/16	27	338/423
424	Fairlead††	7/16	11	—	—	15/8	41	5/8	16	.13	3.5	11/16	27	338/423
Standard														
137	Eyestraps	3/4	19	—	—	2	51	9/16	14	.32	9	11/2	38	150/365
145	Cam wedge kit	—	—	—	—	29/16	65	11/4	32	1.00	28	11/2	38	150/365
201	Low-profile eyestraps	3/8	10	—	—	17/8	48	7/16	11	.16	4.5	11/2	38	150/365
295	Flat cam riser	—	—	1	28	29/16	65	11/4	32	1.50	38	7/8	22	150/365
296	15° Angled cam riser	—	—	1	25	29/16	65	11/4	32	1.25	35	11/2	38	150/365
298	Wire fairlead	—	—	11/4	32	29/16	65	11/4	32	.50	14	11/2	38	150/365
328	Fairlead	11/16	17	—	—	2	51	29/16	65	1.00	28	11/2	38	150/365
375	X-Treme Angle Fairlead†	15/16	24	—	—	113/16	46	29/16	65	1.92	56	11/2	38	150
380	X-Treme Angle Fairlead†	15/16	24	—	—	113/16	46	29/16	65	1.92	56	11/2	38	365
425	Fairlead††	5/8	16	—	—	23/16	56	13/16	21	.25	7	11/2	38	150/365
431	Colored cam caps††	blue/yellow/green/black												150/338/365/423
438	Cam adapter plate	—	—	9/16	14	3	76	17/16	36	2.50	71	11/2	38	150/365
Offshore														
282	Large eyestraps	15/16	23	—	—	213/16	71	3/4	19	.80	23	21/16	52	280
283	Offshore cam wedge kit	—	—	—	—	33/8	85	11/2	38	1.50	43	21/16	52	280

†Max line Ø: 3/8" (10 mm)    †† Indicate color: BL (blue), Y (yellow), G (green), B (black)