

Cam Bases

NEW: 462

Use cam swivel bases when leads must rotate to face the trimmer.

Ball bearing swivel bases feature dual rows of Delrin® ball bearings that swivel freely even under high loads. Bases include stand-up springs and a U-adaptor to accept a variety of appropriate blocks.

The 144 is the standard configuration with a tall arm. It is ideal for mounting in the cockpit or for use on larger keel boats and small offshore boats that use 3.00 in (76 mm) plastic blocks. The low-profile 205 is used when installation is at deck level and when smaller blocks are used. The 1574 accepts Midrange blocks.

The 216 features a second cleat for lines led vertically through the base of the swivel. It is frequently used to combine vang or backstay controls in the same swivel base that handles the mainsheet.

The 240 and 241 are simple swivel bases for main and jib sheets on very small boats or for control lines on boats of all sizes.

The 402 and 403 are fitted with a double cam for use in two-speed mainsheet systems.

The 462 swivel base with 338 Micro Cam-Matic® provides precise cleating. The 16 mm sheaves feature low-friction stainless steel ball bearings to handle high loads. Ideal for controls where cleating angles change dramatically.

Use for:
Mainsheets
Jib sheets
Control lines



Part No.	Description	Height		Weight		Line Ø				Fastener spacing		Safe working load		Use with
		in	mm	oz	g	Min	Max	in	mm	in	mm	lb	kg	
144	Swivel base/150 Cam-Matic®*	5¾	146	13	369	⅛	3 ½	12	¾	19	—	—	—	57mm/75mm/2.25"/3.00"/ratchets
205	Little swivel base/150 Cam-Matic®*	4½	114	12	340	⅛	3 ½	12	¾	19	—	—	—	57mm/Big Bullet/Dinghy/2.25"/little ratchets
216	Duocam swivel base/365, 423 Carbo-Cam®*	5¾	146	16	454	—	—	—	¾	19	—	—	—	57mm/2.25"/3.00"/ratchets
238	150 Cam-Matic® on plate/bullseye‡	1⅝	33	4	113	⅛	3 ½	12	1½/1	38/25	300	139	—	—
239	365 Carbo-Cam® on plate/bullseye‡	1⅝	33	3	85	⅛	3 ¾	10	1½/1	38/25	200	91	—	—
240	Bullseye swivel base/150 Cam-Matic®*	1⅝	49	7.5	213	⅛	3 ½	12	1½/32	26	300	136	—	—
241	Bullseye swivel base/365 Carbo-Cam®*	1½	38	6½	184	⅛	3 ¾	10	1½/32	26	150	68	—	—
360	Swivel base/Trigger cleat*	5½	138	15.25	433	⅛	3 ½	12	¾	19	—	—	—	57mm/75mm/2.25"/3.00"/ratchets
361	Little swivel base/Trigger cleat*	4⅝	110	14	398	⅛	3 ½	12	¾	19	—	—	—	Big Bullet/Dinghy/2.25"/little ratchets
379	423 Micro Carbo-Cam® on plate/bullseye‡‡	⅞	22	1.75	50	⅛	3 ¼	6	1½/16	27	150	68	—	—
402	Small swivel base/412 Cam-Matic®*	4¾	111	12.75	362	⅝	8 ⅞	11	¾	19	—	—	—	57mm/2.25" Double ratchets
403	Swivel base/412 Cam-Matic®*	5¾	146	14	398	⅝	8 ⅞	11	¾	19	—	—	—	57mm/2.25"/3.00" Double ratchets
462	Swivel base/338 Micro Cam-Matic®/16 mm sheaves	1⅝	46	4.8	136	⅛	3 ¼	6	1½/32	26	200	91	—	—
1574	Midrange swivel base/280 Cam-Matic®**	5⅝	151	23	652	¼	6 ⅝	16	1½/16	27	—	—	—	Midrange

*#10 (5 mm) FH fastener **¼" (6 mm) FH fastener ‡#10 (5 mm) RH fastener ‡‡#8 (4 mm) RH fastener