


Installation drawing of Westerbeke L-25 with 2:1 short profile freewheeling sailing gear. Weight 25 pounds. Turns right hand propeller. Short profile gear also available with vee drive, 2:1 or 2.6:1 reduction.



SPECIFICATIONS

Type: Four cylinders in line, four cycle fresh water cooled diesel.

Displacement: 97.6 cu. in. Bore 3.189" (81 mm), stroke 3.055" (77.6 mm).

Power: 22 hp at 2400 rpm (see power curve).

Compression Ratio: 18:1.

Weight: 334 lbs. basic engine. Add gear weights above for IOR weight.

Fuel Injection Equipment: CAV distributor type injection pump

and nozzles. Direct injection combustion chambers.

Cylinder Block: Strongly ribbed cast iron.

Cylinder Head: Cast iron with large cooling water passages. Crankshaft: Forged steel, counter balanced. Drilled holes

conduct oil to all bearing journals.

Main Bearings: Five, 21/8" diameter, for maximum crankshaft support. Camshaft: Heat treated forged steel. Three supporting bearings.

Pistons: Forged aluminum. Two compression rings, one oil control ring.

Connecting Rods: Heavy duty forged steel.

Lubrication: Externally mounted camshaft-driven pump. **Mounting:** Adjustable flexible mounts on 20" centers.

Exhaust Manifold: Fresh water cooled.


Cooling System: Closed circuit fresh water system. Heat exchanger, fresh and raw water pumps mounted on engine.

Angle of Installation: 12° maximum.

Electrical System: 12-volt negative ground system with

45-ampere alternator standard.

Transmission: See above for specifications and propeller rotation.



FUEL RETURN CONN.

3/16 I. DIA. HOSE

18.00.

10.00

STANDARD EQUIPMENT

Fresh water cooling system with heat exchanger, surge tank and pumps mounted on engine, adjustable flexible mounts; propeller shaft coupling; clutch lever with lower extension for remote control where applicable: spin-on full flow lube oil filter, sump pump and hose; flexible fuel hoses for supply and return, engine-mounted secondary fuel oil filter, fuel lift pump with hand primer, hydraulically governed fuel injection system; 12-volt 45-ampere alternator with transistor regulator; plug-in engine pre-wiring including pre-wired start panel with 10-foot cable; threaded 1½" IPS exhaust flange; fully illustrated Instruction Manual and Parts List.

OPTIONAL EQUIPMENT

High efficiency primary fuel filter with water alarm; water-injected exhaust elbow; Hydro-Hush stainless steel water lift muffler; pre-wired all-electric instrument panel with 10-foot cable; extra 10-foot cable for instrument panels or starting panel; high water temperature, low oil pressure alarm system; flexible shaft coupling; special engine mounts, spare parts kits.

WESTERBEKE L-25

The WESTERBEKE L-25 is the lightest diesel for its power you can buy. It is the first diesel able to compete with gasoline engines on a performance per pound basis. Even with fresh water cooling, 2:1 reduction gear, adjustable, flexible mounts and plug-in engine pre-wiring, the L-25 weighs about the same as gasoline engines of similar performance.


The WESTERBEKE L-25 is one of the smoothest and quietest diesel engines we have ever seen. Although light, it is strong where it counts, dependable and durable.

The WESTERBEKE L-25 is available with direct drive, built-in lightweight 2:1, or a vee drive, making it sufficiently versatile for most boats in the 30–38 foot range. If you want a lightweight, durable, and quiet diesel with Westerbeke reliability, try the WESTERBEKE L-25.

Westerbeke marine engines and related products are sold and serviced by Westerbeke distributors in major port cities in North America.




THE WESTERBEKE CORP.





Features:


- Lightweight, about the same as a gasoline engine of similar performance.
- Rugged and Dependable, strong where strength is needed.
- Ideal for Ocean Racers, where weight is important.
- Smooth and Quiet for cruising.

C & C 38










Installation Drawings of WESTERBEKE L-25 with standard direct drive. Gear weighs 26 pounds, turns left hand propeller.

Westerbeke Short Profile Sailing Gear with built-in 2:1 reduction. Weighs 25 pounds, turns right hand propeller.



Vee Drive, 2:1 or 2.6:1 reduction. Weighs 66 pounds, turns left hand propeller.

SPECIFICATIONS

Type: Four cylinders in line, four cycle fresh water cooled

Displacement: 97.6 cu. in. Bore 3.189" (81 mm), stroke 3.055" (77.6 mm).

Power: 22 hp at 2400 rpm (see power curve).

Compression Ratio: 18:1.

Weight: 334 lbs. basic engine. Add gear weights above for

Fuel Injection Equipment: CAV distributor type injection pump

and nozzles. Direct injection combustion chambers.

Cylinder Block: Strongly ribbed cast iron.

Cylinder Head: Cast iron with large cooling water passages. Crankshaft: Forged steel, counter balanced. Drilled holes

conduct oil to all bearing journals.

Main Bearings: Five, 21/8" diameter, for maximum crankshaft support.

Camshaft: Heat treated forged steel. Three supporting bearings.

Pistons: Forged aluminum. Two compression rings, one oil control ring.

Connecting Rods: Heavy duty forged steel.

Lubrication: Externally mounted camshaft-driven pressure pump. Full flow spin-on lube oil filter.

Mounting: Adjustable flexible mounts on 20" centers. Special

mounts available on request.

Exhaust Manifold: Fresh water cooled.

Cooling System: Closed circuit fresh water system. Heat exchanger, fresh and raw water pumps mounted on engine.

Angle of Installation: 12° maximum.

Electrical System: 12-volt negative ground system with

45-ampere alternator standard.

Transmission: See above for specifications and propeller rotation

STANDARD EQUIPMENT

Fresh water cooling system with heat exchanger, surge tank and pumps mounted on engine, adjustable flexible mounts; propeller shaft coupling; clutch lever with lower extension for remote control where applicable: spin-on full flow lube oil filter, sump pump and hose; flexible fuel hoses for supply and return, engine-mounted secondary fuel oil filter, fuel lift pump with hand primer, hydraulically governed fuel injection system; 12-volt 45-ampere alternator with transistor regulator; plug-in engine pre-wiring including pre-wired start panel with 10-foot cable; threaded 11/4" IPS exhaust flange; fully illustrated Instruction Manual and Parts List.

OPTIONAL EQUIPMENT

High efficiency primary fuel filter; water-injected exhaust elbow; Hydro-Hush stainless steel water lift muffler; pre-wired all-electric instrument panel with 10-foot cable; extra 10-foot cable for instrument panels or starting panel; high water temperature, low oil pressure alarm system; flexible shaft coupling; special engine mounts, spare parts kits.

WESTERBEKE L-25

The WESTERBEKE L-25 is the lightest diesel for its power you can buy. It is the first diesel able to compete with gasoline engines on a performance per pound basis. Even with fresh water cooling, 2:1 reduction gear, adjustable, flexible mounts and plug-in engine pre-wiring, the L-25 weighs about the same as gasoline engines of similar performance.

The WESTERBEKE L-25 is one of the smoothest and quietest diesel engines we have ever seen. Although light, it is strong where it counts, dependable and durable.

The WESTERBEKE L-25 is available with direct drive, built-in lightweight 2:1, or a vee drive, making it sufficiently versatile for most boats in the 30-38 foot range. If you want a lightweight, durable, and quiet diesel with Westerbeke reliability, try the WESTERBEKE L-25.

Westerbeke marine engines and related products are sold and serviced by Westerbeke distributors in major port cities in North America.



J. H. WESTERBEKE CORP.

AVON INDUSTRIAL PARK, AVON, MASS. 02322 • (617) 588-7700

CABLE: WESTCORP, AVON . TELEX: 92-4444